



**Product Description:**

Offers excellent image density & long-self life  
 Offers the fastest image built up in any temperature  
 The darkest & clearest image in the industry

**End Application:**

Invoices, Statements, Purchase orders, Contracts, Medical forms, Credit application  
 Expense reports, Dispatch notes, Packing slips , Production orders, etc.

**TECHNICAL SPECIFICATION FOR CARBONLESS PAPER**

| Parameter          | UoM              | Test Method   | CB 75            | CFB 75    | CF 75     |       |
|--------------------|------------------|---------------|------------------|-----------|-----------|-------|
| Basis Weight       | g/m <sup>2</sup> | ISO 536: 2012 | 75 ± 4%          | 75 ± 4%   | 75 ± 4%   |       |
| Thickness          | µm               | Iso 534: 2011 | 98 ± 4           | 95 ± 4    | 95 ± 4    |       |
| Bendtsen Roughness | ml/min           | TS<br>BS      | ISO 8791-2: 2013 | ≤ 300     | ≤ 300     | ≤ 300 |
|                    |                  |               |                  | ≤ 450     | ≤ 450     | ≤ 300 |
| Porosity           | ml/min           | ISO 5636/3/92 | -                | -         | ≤ 250     |       |
| Moisture           | %                | T412 om-94    | 6.0 ± 0.5        | 6.0 ± 0.5 | 6.0 ± 0.5 |       |
| Curling, mm TS/BS  | %                |               | ≤ 8              | ≤ 8       | ≤ 8       |       |


| Print Contrasts | Color  | CB Blue Image       | CB Black Image      | CFB Blue Image      |                     | CFB Black Image     |                     | CF                  |                     |
|-----------------|--------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
|                 |        | Ply 2 <sup>nd</sup> | Ply 2 <sup>nd</sup> | Ply 2 <sup>nd</sup> | Ply 6 <sup>th</sup> | Ply 2 <sup>nd</sup> | Ply 6 <sup>th</sup> | Ply 2 <sup>nd</sup> | Ply 6 <sup>th</sup> |
|                 | White  | ≥ 33                | ≥ 33                | ≥ 33                | ≥ 25                | ≥ 32                | ≥ 25                | ≥ 33                | ≥ 28                |
|                 | Yellow | ≥ 33                | ≥ 33                | ≥ 33                | ≥ 26                | ≥ 32                | ≥ 26                | ≥ 33                | ≥ 29                |
|                 | Blue   | ≥ 33                | ≥ 33                | ≥ 33                | ≥ 25                | ≥ 32                | ≥ 25                | ≥ 33                | ≥ 27                |
|                 | Pink   | ≥ 33                | ≥ 33                | ≥ 33                | ≥ 26                | ≥ 32                | ≥ 26                | ≥ 33                | ≥ 29                |
|                 | Green  | ≥ 33                | ≥ 33                | ≥ 33                | ≥ 25                | ≥ 32                | ≥ 25                | ≥ 33                | ≥ 27                |

TS: Top side; BS: Back Side

**Format** Sheets, Reels & Cut size

**Print Process** Offset

**Image** Blue Image & Black Image

**Color Available**   
 White Yellow Green Pink Blue

MOQ : 3MT per SKU  
 Machine Deckle : 2170 mm



Strategic Sales Channel - USA & Latin America  
 www.chartaglobal.com  
 Email: info@chartaglobal.com  
 Phone: +1 714-687-6648

