


## Foopak Grease Proof with Hardsize

Is an oil / grease resistant white back folding box board, which is functionally designed with the capabilities of paper board for food packaging in fridges appliances.



DOUBLE COATING	Min 20gsm Blade
TOP LAYER	NBKP + LBKP
UNDER LAYER	BCTMP
FILLER LAYER	BCTMP
BACK LAYER	NBKP + LBKP
BARRIER COATING	

## TECHNICAL DATA SHEET / PRODUCT SPECIFICATION

### BASEBOARD PROPERTIES

GRAMMAGE T 410 om - 02	THICKNESS ISO 534:1988 [E]		STIFFNESS TABER 15 <sup>0</sup> T 489 om-04			
	[g/m <sup>2</sup> ]	[µm]	[pt]	CD (gf.cm)	MD (gf.cm)	CD (mNm)
235 ± 5%	350 ± 4%	13.8 ± 4%	61	121	6.0	11.9
250 ± 5%	380 ± 4%	14.9 ± 4%	83	149	7.1	14.6
265 ± 5%	410 ± 4%	16.1 ± 4%	94	174	8.1	17.2
285 ± 5%	450 ± 4%	17.7 ± 4%	116	220	11.4	21.6
310 ± 5%	500 ± 4%	19.7 ± 4%	149	275	14.6	27.0
335 ± 5%	550 ± 4%	21.7 ± 4%	176	330	17.3	32.4
*) 365 ± 5%	600 ± 4%	23.6 ± 4%	223	380	21.8	33.8

\*) Available Upon Requested

Tolerance for Stiffness : ± 10%

MOISTURE CONTENT T 412 om-02	%	6.0 ± 1
---------------------------------	---	---------

ROUGHNESS T555 om-04	235 gsm	Top	(µm)	Max 1.00
	250 - 365 gsm	Top	(µm)	Max 1.30

BRIGHTNESS ISO 2470 - 1977 [E]	Top	%	90.0 ± 1
-----------------------------------	-----	---	----------

GLOSS 75 ISO 2470 - 1977 [E]	Top	%	50.0 ± 5
---------------------------------	-----	---	----------

INTERNAL BONDING SCOTT 569 pm-00	J/m <sup>2</sup>	Min 120
-------------------------------------	------------------	---------

WATER ABSORPTION T441 om-04	COBB (60s)	Top	g/m <sup>2</sup>	35 - 55
	COBB (180s)	Top	g/m <sup>2</sup>	70 (+10)

### APPLICATION USES

Kit 6, 8 : Chocolate, Cake, Bread, Take-Away Box

Kit 10 : Frozen Cake, Frozen Bread, Food Tray, Take Away Box

### COATING OPTIONS

- Available Kit 6, 8, 10
- Kit 6, 8 : Waterbase Glue
- Kit 10 : Special Acrylic & Hotmelt Glue

### RECOMMENDATE PRINTING METHODS

Offset Litho, Letterpress

### OTHER FEATURES

- High Bulk GC1 Substances, Suitable for direct food packaging
- Minimum Moisture Evaporation, Very good dimensional stability
- Grease resistant (to Kit 10), Environment Friendly
- EN 14338 microwave certifications

